

Official Community Plan

DPA No. 12 Mcloughlin Point

Area

Development Permit Area No. 12 applies only to Lot 1, Section 11, Plan EPP36468. PID 030-006-813

Designation

Development Permit Area No. 12 is designated for the purpose of establishing objectives for:

- Section 488 (1)(a)- Natural environment, its ecosystems and biological diversity;
- Section 488 (1)(b)- Protection of development from hazardous conditions;
- Section 488 (1)(d)- Form and character, revitalization of an area in which a commercial use is permitted;
- Section 488 (1)(f)- Form and character of industrial development;
- Section 488 (1)(h)- Energy conservation;
- Section 488 (1)(i)- Water conservation; and
- Section 488 (1)(j)- GHG emissions. *Note: For DPA justification and exemptions please refer to the Official Community Plan, pages 142-143. For photographic examples relevant to the guidelines below, please refer to pages 144-151 of the Official Community Plan.*

If you are proposing a development within this DPA, please provide your application details in Section A. In Section B, please comment on how you propose to meet the DPA guidelines.

Section A

Application No.	Project Address	Applicant Name
DP		

Section B

No.	Guideline	Comments
1	Consider the establishment of an 8.0 m buffer from the high watermark.	
2	Consider the establishment of a 4.0 m heavily landscaped buffer within the 8.0 m buffer to hide the building(s) on the site.	
3	Consider stepping buildings back on the site with the lowest buildings located closest to the shore.	
4	Consider the establishment of a seawall using as its design precedent, the convention centre in Seattle.	




DPA No. 12 McLoughlin Point

5	Consider the establishment of an historical interpretation program.	
6	Consider the establishment of public access to the 8.0 m buffer area via a public dock.	
7	Consider the incorporation of water features as public art within the design of the building.	
8	Consider design and construction in a manner that mitigates environmental and human health impacts (in particular those related to odour and noise), and contributes to the visual quality and scenic beauty of the harbour entrance.	
9	Any proposed buildings or structures must incorporate the findings of the “Modelling of Potential Tsunami Inundation Limits and Run-up” for the Capital Region that has been completed by the Capital Regional District’s Local Government Emergency Program Advisory Commission.	
10	The treatment system will support environmental, social and economic sustainability, and be considered part of CRD climate action initiatives.	
11	Wastewater should be treated as a resource and, wherever possible and practical, provide opportunities for resource recovery and reuse.	
12	The McLoughlin Point facility should meet, or exceed the CRD’s and the Township of Esquimalt’s policies on sustainability and building excellence.	
13	Acknowledge and plan for major tsunami events, climate warming effects, and post-disaster resiliency.	
14	Incorporate durable, long-lasting, and timeless materials and design strategies.	



DPA No. 12 Mcloughlin Point

15	Respect view impacts from all sides, and from above.	
16	Incorporate designs that, while respecting the site, ensure the highest standards of materials and workmanship, and are aesthetically pleasing.	
17	Incorporate public art into the design.	
18	Where feasible, design for on-site heat recovery, and plan for future, long-term, neighbourhood, heat-resource opportunities.	
19	Incorporate a green roof system into the Operations and Controls building and other buildings, where appropriate.	
20	While much of the site is impervious rocky shoreline, where possible, introduce methods to clean and reduce stormwater runoff, incorporate rain gardens, and consider practical ways to re-use water.	
21	Restrict impact on the shoreline, except for those areas where wastewater lines enter or exit the treatment plant.	
22	Building forms should respect the site.	
23	Wall elements, relating to tsunami and associated catastrophic event protection, such as stepped walls that incorporate angled features, projections, wall terraces, and textures, should reflect the character of the rocky shoreline.	
24	The design must demonstrate how the buildings and structures will fit into the site, responding to the shoreline in the forefront, and the evergreen treeline and rocky knoll backdrop.	



DPA No. 12 Mcloughlin Point

25	Building heights should vary, but not exceed 15 m, from the finished grade.	
26	Design aesthetics should be optimized with the use of appropriate, high quality materials.	
27	Exterior building materials, including exterior details, must be selected to withstand intense weather and sea conditions, and must be of a high standard to ensure low maintenance.	
28	Doors, overhead doors, and other closures (including hatches, grilles, and louvres) should be durable, thermally resistant, and suitably finished for the marine environment.	
29	Windows should have high performance glazing, and be capable of providing natural ventilation, where appropriate.	
30	Roof areas must consider views from above.	
31	Clarifiers and aerated filters must be covered to meet noise and odour principles.	



DPA No. 12 Mcloughlin Point

Lighting	
1	Light fixtures should provide no more than the minimum lighting needed for their intended purposes, and not exceed levels recommended by the Illuminating Engineering Society for North America Recommended Practice Manual: Lighting for Exterior Environments.
2	Light fixture shields should be specified to reduce impacts on other properties, and when seen from the designated viewpoints.
3	All lighting should be directed downward, and not into the night sky.
4	Energy efficient fixtures should be specified, with consistent colour for all lighting.

Landscape Elements	
1	<p>The design concept is based on site conditions, views from the harbour, and a windswept rocky shoreline. With this in mind, landscape elements should include:</p> <ul style="list-style-type: none"> • Use of plant species that are designated hardy to harsh, and for sea spray environments - situate plants such that the force of the wind shapes their future forms; • A retaining wall system designed to reflect the rugged and rough-textured surface of boulders and exposed-rock shorelines; and • Outdoor storage and parking areas screened through the use of berms, fences, landscaping and/or solid noise-absorbing barriers.



DPA No. 12 Mcloughlin Point

Guidelines for Seawalls and Walls	
	<p>The retaining wall system should be designed to reflect the rugged and textured surface of the exposed-rock shorelines. To reduce view impacts for neighbouring communities and water/air traffic, the mass of the wall (combined height and width) will be broken up visually with features such as board form relief, wall projections, vertical elements, and wall protrusions. It should feature both rounded, smooth and angular surfaces to reflect the natural shoreline.</p> <p>Walls are divided into two types: 1) primary walls, which are prominent perimeter retaining walls, and feature walls within the plant; and 2) secondary walls, which serve as infill between the primary walls.</p>
1	Walls must not protrude beyond the high watermark (HWM 1.804m geodetic).
2	The site must be protected by a continuous tsunami protection wall that has a top elevation of not less than 6.5 m above the high watermark.
3	The appearance of wall heights greater than 4.0 m must be minimized by placing step walls in the tsunami protection wall.
4	Planted stepped walls should be a minimum depth of 1.0 m horizontally to allow for landscape elements to be introduced. Where this is not possible, shallower multiple steps may be used.
5	All surfaces of the primary perimeter retaining walls must be finished with random board- formed recesses or other suitable architectural treatment. Vertical recesses should be spaced randomly. A smooth finish should be considered for secondary walls.
6	The design should plan for development of a pedestrian pathway along the waterfront side of the site.



DPA No. 12 Mcloughlin Point

Guidelines for Planting- General		
1	Distribution of plants will be limited due to sea spray and wind exposure, particularly on the south side of the site.	
2	Planting will exclude lawns.	
3	Mature plant heights must be at least 60 cm tall for all planted areas to shade undesirable weed species.	
4	Planting densities must ensure that vegetated areas will have 100% plant coverage after two full growing seasons.	
5	Planted areas will be irrigated with a high efficiency irrigation system.	
6	Plants should be drought tolerant and require minimal water after the two-year establishment period.	
7	Green roofs must be installed fully established to minimize wind erosion and maintenance.	
8	All planting will be to BCNLA/BCSLA Landscape Standards.	

Guidelines for Planting Along Seawalls		
1	Distribution of plants will be limited due to sea spray and wind exposure.	
2	Trees must be situated more than 10 m from the south facing wall, as this will be a high wind velocity area.	



DPA No. 12 Mcloughlin Point

3	<p>The following species are considered appropriate for use along the waterfront:</p> <ul style="list-style-type: none"> • Pinus contorta var. Contorta (Shore Pine); • Arbutus menzesii (Pacific Madrone); • Rosa nutkana (Nootka Rose); • Symphoricarpus albus (Snowberry); • Arbutus unedo (Strawberry Tree); • Myrica californica (Sweet Gale); • Lonicera pileata (Privet Honeysuckle); and • Mahonia aquifolium (Oregon Grape) 	
---	--	--

	Guidelines for Planting Adjacent to Building Entrances	
	Planting around the building entrances can be more design driven, and specific hard and soft landscaping should complement the building architecture.	


	Guidelines for Screening on Victoria View Road	
1	To break up the mass of concrete walls, introduce screening (mostly of coniferous tree plantings) along the road frontage and adjacent property lines. The CRD should work with the Department of National Defence to allow for landscaping along the road frontage adjacent to the site. Cluster trees to provide clear 8 m wide gaps to allow for future maintenance access (from a crane).	
2	A continuous shrub border will be required at the base of the wall to screen the lower retaining wall and reduce the risk of vandalism. Shrubs in this area are to be native species only, with the exception of those adjacent to the two entrances, where lower evergreen screening is desirable.	



DPA No. 12 Mcloughlin Point

3	In situations with larger retaining walls, vines can be considered, but must be supported by cable systems.	
4	<p>The following species are considered appropriate for use in screening applications:</p> <ul style="list-style-type: none"> • Pseudotsuga menziesii (Douglas Fir); • Rosa nutkana (Nootka Rose); • Symphoricarpus albus (Snowberry); and • Parthenocissus tricuspidata (Boston Ivy). 	

	Stormwater Management	
1	Stormwater from the internal roadways and parking areas will be treated to remove 80% of TSS from a 6-month rain event prior to discharge.	
2	<p>Treatment of roadway and parking run-off can come in the form of:</p> <ul style="list-style-type: none"> • A combination of rain gardens and bioswales adjacent to the parking and roadways, complete with raised overflow basins, and under drains connected to the storm drain system; • Aqua-pave permeable paving, complete with an under drain system in discrete areas where direction of run-off to a bioswale is not feasible; or • A combination of these. 	
3	A conventional storm drain will be installed with an outfall to the ocean. All drainage from the site will eventually be discharged through this pipe.	
4	The buildings will connect directly to the piped storm drain system. Building drainage will bypass the treatment system. However, a rain garden, stormceptor, or similar end-of-pipe treatment device could be installed if treatment of roof drainage is required.	



DPA No. 12 Mcloughlin Point

	Parking and Services	
	<p>Parking for visitors, plant and system operation staff, and CRD maintenance vehicles should be suitably screened through the use of berms, fences, landscaping and/or solid noise-absorbing barriers to minimize visual impact.</p>	

	Signage	
	<p>Limit signage to directional and identification as required for wayfinding.</p>	

	Public Art and Education	
1	<p>Public art shall be provided. The CRD and Township of Esquimalt will work together to confirm the process and requirements.</p>	
2	<p>Plans should include capacity for organized, educational site visits to learn about the functioning of the treatment system, the regional liquid waste management program, resource recovery, etc</p>	